

 FALLTECH®



FT-R[™]
LEADING EDGE

FallTech® introduces the new FT-R™ Class 2 Leading Edge Series 20', 30', and 60' SRL's engineered for those who require the optimal balance of compliance, safety, and worker efficiency when working at height.

30' Class 2 Leading Edge

FT-R™ SRL



Anchorage Location Flexibility

Anchor overhead or up to 5 feet below the user's dorsal D-ring. Performance in all orientations and locations where you need it.



Convenience Where It Counts

Includes swiveling anchorage point connection, swiveling locking carabiner, and integrated carrying handle to simplify installation and transportation.



Smallest & Lightest Class 2 SRL on the Market

Revolutionary design reduces weight and size dramatically while maintaining smooth operation for the ultimate user experience.



Optimized Lock-Up Speed

Improved internal mechanism design minimizes unintentional lockups to keep you moving freely and productively.




Innovative Energy Absorber Design

More consistent and predictable performance in all conditions. Features full fall clearance diagrams and charts inside the energy absorber.



UV- & Scratch Resistant Label

Industry first UV-resistant label with scratch/scrape/scuff protection to keep labels legible in the harshest working environments



ANSI Z359.14-2021 Class 2 Compliant

Suitable for below D-ring tie-off up to five feet and leading edge exposures and hazards.

721530LE

FallTech® introduces the new FT-R™ Class 2 Leading Edge Series 20', 30', and 60' SRL's engineered for those who require the optimal balance of compliance, safety, and worker efficiency when working at height.



| 721520LE



| 721530LE



| 721560LE

Performance Specifications	
ANSI SRL Class/Type	Class 2 SRL
Maximum Arrest Force	1,800 lb
Average Arrest Force	1,575 lb or less
Maximum Arrest Distance	42 in or less
Static Strength	3,600 lbs. Minimum
ANSI User Capacity	One User up to 310 lbs. Max
OSHA User Capacity	One User up to 310 lbs. Max

Material Specifications	
Housing	Glass Reinforced Nylon
Cable	7/32" Galvanized Steel Wire Rope 3,600 lb min. strength
Lifeline Connector	Plated Alloy Steel 5,000 lb min. strength with 3,600 lb min. gate strength
Anchorage Connector	Plated Alloy Steel 5,000 lb min. strength with 3,600 lb min. gate strength

Part #	Weight	Length
721520LE	13.6 lbs	20'
721530LE	15.8 lbs	30'
721560LE	26.0 lbs	60'

Relevant Standards	
ANSI	Z359.14-2021 Class 2
OSHA	1926.502, 1910.140

Discover the full selection of all
our fall protection products at
www.falltech.com



Tel / 323.752.0066

Fax / 323.752.5613

**©2022 Alexander Andrew, Inc
1306 S. Alameda St. Compton,
CA. 90221-4803**

Tools shown not included.

Product description and specifications
herein may change without notice.

U.S. and International Patents Pending.

Part #480-00049

