



**GUARDIAN®**

HALO CABLE SRL-LE

Self-Retracting Lifeline

A longstanding and trusted leader in the world of Leading Edge applications, the Halo SRL-LE is recognized throughout the industry for its superior performance. It has evolved over the years to incorporate the features workers want the most, and is the go-to SRL-LE for customers across the nation.

The original SRL-LE from Guardian

**HEIGHT SAFETY.
SIMPLIFIED.**

guardianfall.com



HALO CABLE SRL-LE

Self-Retracting Lifeline



Key features & benefits

Swivel top connection point

Swivels 360 to ensure the unit remains in the best orientation, prevents lifeline snagging or tangling

Aluminum housing

Super lightweight & extremely durable

Rubber boot

Protects housing and labels from damage, impacts, and scraping

Rubber lifeline stopper

Doubles as a convenient hand-grip

Steel cable lifeline

Resists cuts and abrasions

Integrated shock absorber

1,350 lbs of average arresting force

Fall-indicating swivel snap hook

Shows if SRL has been exposed to an impact

Carabiner included

Specifications

User weight range (LE use) | 130-310 lbs

User weight range (Non-LE use) | 130-420 lbs

Materials | Polyester, nylon, stainless steel, & rubber



Part number	Description	Hook type	Length	User Weight Range
10920	Class B, cable SRL	Steel swivel snap hook	20'	See specifications
10922	Class B, cable SRL	Steel swivel snap hook	25'	See specifications
10924	Class B, coated-cable SRL	Steel swivel snap hook	50'	See specifications
10925	Class B, cable SRL	Steel swivel snap hook	30'	See specifications
10927	Class B, cable SRL	Steel swivel snap hook	50'	See specifications
10928	Class B, cable SRL	Steel swivel snap hook	65'	See specifications

Declaration of conformity

This product has been tested in an ISO 17025 certified laboratory in accordance with all requirements specified by ANSI Z359.7-2019. All testing is validated by a third party professional engineer.

This product is compliant with the following safety regulations:
ANSI Z359.14-2014 | OSHA 1910.140 & 1926.502

For more information:

+1 (800) 466 6385

info@guardianfall.com



Designed, tested, and assembled in the **United States**