

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

B1120149

Declaration Date

11/20/2020

Tested Item #

7016BFDM

Additional Items Conforming Under this Declaration:

7016BFDXS 7016BFDS 7016BFDL 7016BFDXL 7016BFD2X 7016BFD3X

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

ANSI Z359.11-2014

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2005

Supporting
Documentation

PC-2065

Authorized Signature

Name

Zachary Winters

Title

Engineering Manager

Date

11/20/2020



International Accreditation Service, Inc
3060 Saturn St, Ste 100
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594
ISO/IEC 17025:2017
Alexander Andrew Inc dba FallTech

FallTech Test Report

Test Report No.	PC-2065	Rpt. Date	11/20/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6				
Part No.	7016BFDM	Part No. Revision	A				
Part Description	Contractor+ FBH 2D Climbing Non-belted, Medium, TB Legs/MB Chest						
Test Request No.	PC-2065	Date Complete	11/19/2020				
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

Material/Sample Identification

Sample ID	Description
5614431	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614422	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614419	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614425	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614423	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614424	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614421	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614428	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614435	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614430	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614434	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614436	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614437	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614427	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614429	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614432	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614438	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest
5614426	FT-Iron Full Body Harness 3D Construction Belted, Dual Size S/M, QC Legs/QC Chest

Test Summary

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2014 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf \geq 1 Minute	3641.3 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2014 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf \geq 1 Minute	3633.5 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass



FallTech Test Report

Test Report No.	PC-2065	Rpt. Date	11/20/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6				
Part No.	7016BFDM	Part No. Revision	A				
Part Description	Contractor+ FBH 2D Climbing Non-belted, Medium, TB Legs/MB Chest						
Test Request No.	PC-2065	Date Complete	11/19/2020				

Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2014 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf \geq 1 Minute	3630.2 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2014 4.3.5	Static Strength (Sternal D-ring)	3600 Lbf \geq 1 Minute	3662.9 Lbf	Pass
	Static Strength (Sternal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2014 4.3.5	Static Strength (Sternal D-ring)	3600 Lbf \geq 1 Minute	3634.9 Lbf	Pass
	Static Strength (Sternal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2014 4.3.5	Static Strength (Sternal D-ring)	3600 Lbf \geq 1 Minute	3629.1 Lbf	Pass
	Static Strength (Sternal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass



FallTech Test Report

Test Report No.	PC-2065	Rpt. Date	11/20/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6				
Part No.	7016BFDM	Part No. Revision	A				
Part Description	Contractor+ FBH 2D Climbing Non-belted, Medium, TB Legs/MB Chest						
Test Request No.	PC-2065	Date Complete	11/19/2020				

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2014 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	5258.4 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq 30^\circ$	2.4°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	11.1"	Pass
ANSI Z359.11-2014 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	5194.8 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq 30^\circ$	1.3°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	11.1"	Pass
ANSI Z359.11-2014 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	5285.3 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq 30^\circ$	1.3°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	11.1"	Pass



FallTech Test Report

Test Report No.	PC-2065	Rpt. Date	11/20/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6				
Part No.	7016BFDM	Part No. Revision	A				
Part Description	Contractor+ FBH 2D Climbing Non-belted, Medium, TB Legs/MB Chest						
Test Request No.	PC-2065	Date Complete	11/19/2020				

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	2476.8 Lbf	*
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	3.5°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	3910.4 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	2.7°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	2292.3 Lbf	*
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	3.3°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

FallTech Test Report

Test Report No.	PC-2065	Rpt. Date	11/20/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6				
Part No.	7016BFDM	Part No. Revision	A				
Part Description	Contractor+ FBH 2D Climbing Non-belted, Medium, TB Legs/MB Chest						
Test Request No.	PC-2065	Date Complete	11/19/2020				

Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2014 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4532.1 Lbf	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Angle at Rest ≤ 50°	22.2°	Pass
	Dynamic Performance Sternal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	8.2"	Pass
ANSI Z359.11-2014 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4460.5 Lbf	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Angle at Rest ≤ 50°	21.8°	Pass
	Dynamic Performance Sternal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	8.2"	Pass

FallTech Test Report

Test Report No.	PC-2065	Rpt. Date	11/20/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.6				
Part No.	7016BFDM	Part No. Revision	A				
Part Description	Contractor+ FBH 2D Climbing Non-belted, Medium, TB Legs/MB Chest						
Test Request No.	PC-2065	Date Complete	11/19/2020				

Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2014 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4272.4 Lbf	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Angle at Rest ≤ 50°	23.6°	Pass
	Dynamic Performance Sternal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	8.5"	Pass
ANSI Z359.11-2014 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2014 4.3.7	Lanyard Parking Attachment Element	Disengagement Load ≤ 120 Lbf	Previously Tested and Passed under PC-0606	Pass


Conclusion

Based upon the samples provided to the Lab:
 FallTech P/N 7016BFDM Rev. A meets the requirements of ANSI Z359.11-2014

Test Exceptions

* Harness has been dynamically tested and subjected to forces of 5,000 Lbs. or more. Energy absorbing properties inherent to the harness prevented residual force readings equal to or greater than the 3,600 Lbs. required by the standard.

Report Signatories and Approval

Lab Quality Manager		Date	11/20/2020
Witnessed by	Not Required	Date	N/A