



Specifications Cordstrap Strapping Solution:

CC Strap 55 Ultraflex & Cordstrap Buckle CB5S

Performance Specifications			
Performance System (Strapping & Buckle)	880 daN / 1940 lbf		
System Breaking Strength (SBS) ¹			
Performance Strapping	550 daN / 1212 lbf		
Linear Breaking Strength ¹			
Elongation at Break			
	12 %		
Certification	DNV witnessed		

Strapping Specifications			
Width ²	16 mm / 0.63"		
Length ²	700 m / 2296 ft		
Core diameter	200 mm / 8"		
Color	white		
Printing	no, printing on request		
Packaging	Quantity	Item number	
Coil	700 m / 2296 ft	7313000	
Cardboard Box	2 coils		
Pallet	60 coils		
Pallet box	n/a		
Material	Recycling symbol/code	Recycled content	Recyclable
High tenacity polyester filament yarn and homopolymer polypropylene	C/PES/PP	0%	No



Represented in over 50 countries
World market leader
ISO 9001:2008 certified
Manufacturer & supplier since 1965
Offering genuine customer solutions

Specialist advice
Continued product development
Training at Cordstrap Training Centers
Quality assurance



Buckle Specifications			
Width ²	16 mm / 0.63"		
Packaging Cardboard Box Pallet	Quantity 1000 pieces per box 64 boxes per pallet	Item number 7373000	
Material Galvanized steel wire	Recycling symbol/code FE/40	Recycled content 70%	Recyclable Yes

Packaging material			
Packaging type	Recycling symbol/code	Recycled content	Recyclable
Cardboard Box	LDPE/04	0%	Yes
Pallet box	PAP/20	80%	Yes
Pallet	PAP/20	80%	Yes

Recommended tensioners
CT 20; CTT 20

¹Tolerance of +/- 10%
²Tolerance of +/- 2%

We recommend storing all Cordstrap Products in a cool and dry environment out of direct sunlight and between -5°C and 40°C / 23°F and 104°F.
 All information provided is based on accuracy at the time of creation.



Represented in over 50 countries
 World market leader
 ISO 9001:2008 certified
 Manufacturer & supplier since 1965
 Offering genuine customer solutions

Specialist advice
 Continued product development
 Training at Cordstrap Training Centers
 Quality assurance