

Specifications Cordstrap Strapping Solution:

CC Strap 65 Ultraflex & Cordstrap Buckle CB6S

Performance Specifications	
Performance System (Strapping & Buckle)	
System Breaking Strength (SBS) ¹	1000 daN / 2204 lbf
Performance Strapping	
Linear Breaking Strength ¹	625 daN / 1377 lbf
Elongation at Break	12 %
Certification	DNV witnessed

Strapping Specifications			
Width ²	19 mm / 0.75"		
Length ²	600 m / 1968 ft		
Core diameter	200 mm / 8"		
Color	white		
Printing	no, printing on request		
Packaging	Quantity	Item number	
Coil	600 m / 1968 ft	7297000	
Cardboard Box	2 coils		
Pallet	60 coils		
Pallet box	n/a		
Material	Recycling symbol/code	Recycled content	Recyclable
High tenacity polyester filament yarn and homopolymer polypropylene	C/PES/PP	0%	No



Represented in over 50 countries

World market leader ISO 9001:2008 certified Manufacturer & supplier since 1965 Offering genuine customer solutions Specialist advice Continued product development Training at Cordstrap Training Centers Quality assurance

Buckle Specifications				
Width ²	19 mm / 0.75"			
Packaging	Quantity	ltem n	number	
Cardboard Box	500 pieces per box	7374500		
Pallet	96 boxes per pallet			
Material	Recycling symbol/code	Recycled content	Recyclable	
Galvanized steel wire	FE/40	70%	Yes	

Packaging material			
Packaging type	Recycling symbol/code	Recycled content	Recyclable
Cardboard Box	LDPE/04	0%	Yes
Pallet box	PAP/20	80%	Yes
Pallet	PAP/20	80%	Yes

Recommended	ensioners	
CT 20; CTT 20;	T 25, CTT 25	

¹Tolerance of +/- 10%

We recommend storing all Cordstrap Products in a cool and dry environment out of direct sunlight and between -5°C and 40°C / 23°f and 104°f.

All information provided is based on accuracy at the time of creation.



Represented in over 50 countries

World market leader ISO 9001:2008 certified Manufacturer & supplier since 1965 Offering genuine customer solutions Specialist advice Continued product development Training at Cordstrap Training Centers Quality assurance

²Tolerance of +/- 2%