

## Specifications Cordstrap composite strap solution: CC Strap 40 & Cordstrap Buckle CB4

Performance Specifications		
Performance System (Strapping & Buckle)		
System Breaking Strength (SBS) <sup>1</sup>	480 daN / 1058 lbf	
Performance Strapping		
Linear Breaking Strength <sup>1</sup>	300 daN / 661 lbf	
Elongation at Break	12 %	
Certification	DNV witnessed	

Strap Specifications: CC Strap 105/6			Item number: 7251000
Width <sup>2</sup>	13 mm / 0.52"		
Length <sup>2</sup>	1100 m / 3608 ft		
Core diameter	200 mm / 8"		
Printing	no, printing on request		
Material	Recycling symbol/code	Recycled content	Recyclable
High tenacity polyester filament yarn and homopolymer polypropylene	C/PES/PP	0%	No
HS code	39219060		
Packaging	Quantity	Weight	Dimension
Coil	1100 m / 3608 ft	11,7 kg / 26 lbs	n/a
Cardboard Box	2 coils	23,5 kg / 52 lbs	400x400x370 mm 16x16x14.8"
Pallet	30 boxes	727 kg / 1603 lbs	1220x800x2000 mm 48.8x32x80"
Pallet box	n/a	n/a	n/a



Represented in over 50 countries

World market leader ISO 9001:2008 certified Manufacturer & supplier since 1965 Offering genuine customer solutions Specialist advice
Continued product development
Training at Cordstrap Training Centers
Quality assurance



Buckle Specifications: CB 4			Item number: 7352000
Width <sup>2</sup>	13 mm / 1.26"		
Packaging	Quantity	Weight	Dimension
Cardboard Box	1000 pcs	10 kg / 22 lbs	200x180x160 mm 8x7x6"
Pallet	96 boxes per pallet	963 kg / 2123 lbs	1200x800x1070 mm 48x32x43"
Material	Recycling symbol/code	Recycled content	Recyclable
Galvanized steel wire	FE/40	70%	Yes

Packaging material			
Packaging type	Recycling symbol/code	Recycled content	Recyclable
Cardboard Box	LDPE/04	0%	Yes
Pallet box	PAP/20	80%	Yes
Pallet	PAP/20	80%	Yes

Recommended tensioners	
CT 20; CTT 20	

<sup>&</sup>lt;sup>1</sup>Tolerance of +/- 10%

We recommend storing all Cordstrap Products in a cool and dry environment out of direct sunlight and between -5°C and 40°C / 23°f and 104°f. All information provided is based on accuracy at the time of creation.



Represented in over 50 countries

World market leader ISO 9001:2008 certified Manufacturer & supplier since 1965 Offering genuine customer solutions Specialist advice
Continued product development
Training at Cordstrap Training Centers
Quality assurance

<sup>&</sup>lt;sup>2</sup>Tolerance of +/- 2%