


A-1337



- Suitable for use with both Grade 80 and Grade 100 chain.
- Individually Proof Tested at 2-1/2 times Working Load Limit with certification.
- Locking system that provides for simple assembly and disassembly - no special tools needed.
- Meets ASTM A-952 standards for Grade 100 chain fittings.
- Forged alloy steel — Quenched & Tempered.
- Sizes 9/32 through 1 inch are fatigue rated.



A-1337 LOK-A-LOY® 10 Alloy Connecting Link

Chain Size		Stock No.	Pkg. Qty.	Weight Each (lb)	Working Load Limit (lb)	Dimensions (in)					
(in)	(mm)					A	B	C	D	E	F
9/32 (1/4)	7	1015104	60	0.29	4300	0.38	1.94	2.00	0.80	0.68	0.53
5/16	8	1015113	50	0.42	5700	0.37	2.36	2.13	0.99	0.72	0.59
3/8	10	1015122	40	0.77	8800	0.51	2.65	2.55	1.09	0.91	0.73
1/2	13	1015136	12	1.60	15000	0.68	3.46	3.39	1.45	1.13	0.89
5/8	16	1015145	10	3.10	22600	0.78	4.25	4.00	1.77	1.34	1.20
3/4	20	1015154	1	6.39	35300	1.01	5.14	5.30	2.15	1.64	1.56
7/8	22	1015163	1	7.85	42700	1.09	5.46	5.78	2.27	1.97	1.55
1	26	1015172	1	11.05	59700	1.24	5.94	6.50	2.41	2.21	1.88
1-1/4	32	1015181	1	21.00	90400	1.56	7.43	7.60	3.07	2.57	2.22

4:1 Design Factor.