



InCord®
Custom Safety Netting Solutions

InCord
226 Upton Road
Colchester, CT 06415

Technical Specifications



RocBloc™ 10K Debris Containment Net

RocBloc 10K Specifications

Structural Netting	N820BK
Fiber	High Tenacity Polypropylene
Cord Diameter	0.187 in (4.75 mm)
Mesh Size	2.5 in (65 mm)
Web Border	4.0 in Polypropylene
Web Reinforcement	2.0 in Polypropylene
Grommets	#2 Stainless Steel 2 ft OC
Net Application Rating	10,000 lb (4500 kg)
FR Rating (optional)	NFPA 701
UV Rating	300 kLy
Color	Black

Debris Liner Options

InCord DNR25BK FR - 1/4"

The polyester medium-mesh liner is highly resistant to abrasion and is resistant to fabric tears. DNR25BK FR provides good air flow and light.

Fiber	Polyester, 1000 Denier
Mesh Size	1/4 x 3/8 inch (6 x 10 mm)
Burst Strength	164 lbf minimum
FR Rating	NFPA 701 Method 1

InCord WS70BK FR - 1/16"

The polyethylene mesh monofilament fiber is light weight and is resistant to fabric tears. WS70 is recommended for small particle containment.

Fiber	High Density Polyethylene
Mesh Size	1/16 inch (1.6 mm)
Burst Strength	210 psi
FR Rating	NFPA 701 Method 2
Shade Factor	70%
Air Permeability	>1480 cfm

Description

RocBloc™ 10K nets are used for the containment of debris, and for use as a safety barrier suitable for walking-working surface personnel protection.

The RocBloc 10K nets when used as a vertical barrier meets the safety requirements of fall protection code OSHA 1926.501.

RocBloc 10K nets are assembled using a two-ply construction method to join a 2-1/2" structural net underlay to a 1/4" or 1/16" debris liner.

The layered panels are joined at the border with 4" reinforced Polypropylene webbing. Stainless steel border grommets are installed two foot on-center along all sides.

RocBloc 10K nets feature red, 2-inch webbing border reinforcements at grommet points.

