



- Made of durable galvanized steel
- Should not be used in high moisture conditions. Stainless steel shackles are recommended for moist conditions

Size	W.L.L.	M.B.S.	A	B	C	D	E	Weight
inch	T	T	mm	mm	mm	mm	mm	kg/pc
1"	8.5	51	42.9	25.4	95.3	28.7	68.3	2.25
1-1/2"	17	102	60.5	39.1	146	41.4	98.6	7.8
1-1/4"	12	72	51.6	32.8	119.1	35.1	82.6	4.2
1-1/8"	9.5	57	46	29.5	107.9	31.8	73.9	3.2
1-3/4"	25	150	73.2	46.7	177.8	50.8	127	12.9
1-3/8"	13.5	81	57.2	36.1	133.3	38.1	92.2	6.01
1/2"	2	12	20.6	12.7	47.8	16	33.3	0.31
1/4"	0.5	3	11.9	6.4	28.7	7.9	19.8	0.05
2"	35	210	82.6	52.8	196.8	57.2	146	18.5
2-1/2"	55	330	104.9	68.8	266.7	69.9	186.1	36.5
3/16"	0.35	2.1	9.7	4.8	22.4	6.4	15.2	0.02
3/4"	4.75	28.5	31.8	19.1	71.4	22.4	50.8	1.05
3/8"	1	6	16.8	9.7	36.6	11.2	26.2	0.14
5/16"	0.75	4.5	13.5	7.9	31	9.7	21.3	0.08
5/8"	3.25	19.5	26.9	16	60.5	19.1	42.9	0.61
7/16"	1.5	9	19.1	11.2	42.9	12.7	29.5	0.18
7/8"	6.5	39	36.6	22.4	84.1	25.4	57.9	1.52