

**RATED CAPACITIES - ENDLESS AND EYE & EYE**

PART CODE	WIDTH	VERTICAL <i>(in lbs)</i>	CHOKER <i>(in lbs)</i>	BASKET <i>(in lbs)</i>	*BASKET 60° <i>(in lbs)</i>	*BASKET 45° <i>(in lbs)</i>	*BASKET 30° <i>(in lbs)</i>
PRS1	0.60"	2,600	2,100	5,200	4,500	3,700	2,600
PRS2	0.80"	5,300	4,200	10,600	9,200	7,500	5,300
PRS3	1.00"	8,400	6,700	16,800	14,500	11,900	8,400
PRS4	1.20"	10,600	8,500	21,200	18,400	15,000	10,600
PRS5	1.30"	13,200	10,600	26,400	22,900	18,700	13,200
PRS6	1.40"	16,800	13,400	33,600	29,100	23,800	16,800
PRS7	1.55"	21,200	17,000	42,000	36,700	30,000	21,200
PRS8	1.75"	25,000	20,000	50,000	43,300	35,400	25,000
PRS9	1.95"	31,000	24,800	62,000	53,700	43,800	31,000
PRS10	2.35"	40,000	32,000	80,000	69,300	56,600	40,000
PRS11	3.15"	53,000	42,400	106,000	91,800	75,000	53,000
PRS12	3.95"	66,000	52,800	132,000	114,300	93,400	66,000
PRS13	4.80"	90,000	72,000	180,000	155,800	127,300	90,000
PRS14	4.80"	100,000	80,000	200,000	173,200	141,400	100,000

\*Rated capacities are determined with the sling angle calculated from the vertical.

