

Rated in US tons



OPTIONAL THIMBLE & HOOK:



ROPE DIA. (in)	RATED CAPACITIES (tons)						EYE SIZE (in)		THIMBLE SIZE (in)		HOOK	
	VERTICAL HITCH	CHOKER HITCH	BASKET HITCH	BASKET HITCH								
				60°	45°	30°	WIDTH	LENGTH	WIDTH	LENGTH	WLL (tons)	MATERIAL
1/4"	0.65	0.48	1.3	1.1	0.91	0.65	2	4	0.88	1.63	3/4	Carbon
5/16"	1	0.74	2	1.7	1.4	1	2.5	5	1.06	1.88	1	Carbon
3/8"	1.4	1.1	2.8	2.5	2	1.4	3	6	1.13	2.13	1-1/2	Carbon
7/16"	1.9	1.4	3.8	3.4	2.7	1.9	3.5	7	1.25	2.25	2	Carbon
1/2"	2.5	1.9	5	4.4	3.6	2.5	4	8	1.5	2.75	3	Carbon
9/16"	3.2	2.4	6.4	5.5	4.5	3.2	4.5	9	1.5	2.75	3	Carbon
5/8"	3.9	2.9	7.8	6.8	5.5	3.9	5	10	1.75	3.25	5	Carbon
3/4"	5.6	4.1	11	9.7	7.9	5.6	6	12	2	3.75	5	Carbon
7/8"	7.6	5.6	15	13	11	7.6	7	14	2.25	4.25	7-1/2	Carbon
1"	9.8	7.2	19.6	17	14	9.8	8	16	2.5	4.5	10	Carbon
1-1/8"	12	9.1	24	21	17	12	9	18	2.88	5.13	10	Carbon
1-1/4"	15	11	30	26	21	15	10	20	2.88	5.13	15	Carbon
1-3/8"	18	13	36	31	26	18	11	22	3.5	6.25	15	Carbon
1-1/2"	21	16	42	37	31	21	12	24	3.5	6.25	22	Alloy
1-3/4"	28	21	56	49	37	28	14	28	4.5	9	37	Alloy
2"	37	28	74	63	49	37	16	32	6	12	45	Alloy
2-1/4"	44	35	88	77	63	44	18	36	7	14	45	Alloy
2-1/2"	54	42	108	94	77	54	20	40	8	17.5	60	Alloy
2-3/4"	65	51	130	113	92	65	22	44				
3"	77	60	154	133	108	77	24	48				

If you don't see the configuration you're looking for on the site, fill out our online form or contact us for a quote.

