






# CHECK-FAST® SINGLE PATH HIGH PERFORMANCE ROUNDSLINGS

Check-Fast® High Performance Roundslings are the only single path HP Roundsling to feature the Check-Fast®, Inspection System. Resilient K-Spec® Core Yarn is encapsulated by Covermax®, contrasting color, double cover Roundsling Covers.

## CHECK-FAST® HIGH PERFORMANCE ROUNDSLING SPECIFICATIONS

Check-Fast® HP Roundsling Stock Number	WORK LOAD LIMITS (Lbs.)					Minimum Connection Diameter (Inches)	Approximate Weight (Lbs. per Ft.) (Bearing- Bearing)	Nominal Body Width (Inches)
	Choker	Vertical	Basket Hitches					
			90° 	60° 	45° 			
SP 500CF	4,000	5,000	10,000	8,660	7,070	.76	.34	2.5"
SP 1000CF	8,000	10,000	20,000	17,320	14,140	.88	.38	2.5"
SP 1500CF	12,000	15,000	30,000	25,980	21,210	1.00	.44	2.5"
SP 2000CF	16,000	20,000	40,000	34,640	28,280	1.26	.52	2.5"
SP 2500CF	20,000	25,000	50,000	43,300	35,350	1.38	.59	3"
SP 3000CF	24,000	30,000	60,000	51,960	42,420	1.50	.65	3"
SP 4000CF	32,000	40,000	80,000	69,280	56,560	1.76	.85	3"
SP 5000CF	40,000	50,000	100,000	86,600	70,700	1.76	.98	4"
SP 6000CF	48,000	60,000	120,000	103,920	84,840	2.00	1.11	4"
SP 7000CF	56,000	70,000	140,000	121,240	98,980	2.25	1.24	4"
SP 8500CF	68,000	85,000	170,000	147,220	120,190	2.50	1.63	5"
SP 10000CF	80,000	100,000	200,000	173,200	141,400	2.75	1.81	5"
SP 12500CF	100,000	125,000	250,000	216,500	176,750	3.00	2.12	5"
SP 15000CF	120,000	150,000	300,000	259,800	212,100	3.00	2.54	6"
SP 17500CF	140,000	175,000	350,000	303,100	247,450	3.50	3.09	6"
SP 20000CF	160,000	200,000	400,000	346,400	282,800	3.50	3.58	6"



**WARNING** See the appropriate section of the Lift-It® Resource Guide for Important Safety, Use and Inspection Information. Dimensions & weights subject to change without notice.