

## TWIN-PATH® EYE & EYE SLINGS

Twin-Path® Eye and Eye Slings are a perfect Slingmax® solution for applications requiring an eye and eye configuration. All the benefits of Twin-Path® are included in the Twin-Path® Eye & Eye Sling, which features a single body and integrated eyes.

TWIN PATH® EYE & EYE SLING SPECIFICATIONS (Capacities in Lbs.)

Stock Number	Choker	Vertical	90° Basket	Weight (Lbs./Ft.)	Width (Inches)
TUFXKS 1000EE	8,000	10,000	20,000	.28	3
TUFXKS 1500EE	12,000	15,000	30,000	.36	3
TUFXKS 2000EE	16,000	20,000	40,000	.50	3
TUFXKS 2500EE	20,000	25,000	50,000	.60	4
TUFXKS 3000EE	24,000	30,000	60,000	.75	4
TUFXKS 4000EE	32,000	40,000	80,000	1.00	4
TUFXKS 5000EE	40,000	50,000	100,000	1.40	5



Please Note: Work Load Limits include both paths and are for one complete sling. Work Load Limits are based upon connection points that have equal or greater strength. Twin-Path® Extra Slings conform to the specifications and standards of: ASME B30-9, Chapter 6, Web Sling and Tie Down Association, WSTDA-RS-1, US Navy, NAVFAC P307, Section 14.6.4.3 and the Cordage Institute Roundsling Standard, CI-1905.

**⚠ WARNING** Slings can fail if damaged, misused, or overloaded. Inspect before use. Damaged slings shall not be used. Do Not Exceed Rated Capacity. Protect sling from being cut by load edges, protrusions, corners and abrasive surfaces. Avoid exposure to damaging chemicals and temperatures over 180 degrees (F). DEATH or INJURY can occur from improper use or maintenance.